

Division of Air Quality  
601 57<sup>th</sup> Street SE  
Charleston, WV 25304  
Phone (304) 926-0475  
Fax (304) 926-0479



west virginia department of environmental protection

Jim Justice, Governor  
Austin Caperton, Cabinet Secretary  
www.dep.wv.gov

## G35-D GENERAL PERMIT ENGINEERING EVALUATION

PREVENTION AND CONTROL OF AIR POLLUTION IN REGARD TO THE CONSTRUCTION, MODIFICATION,  
RELOCATION, ADMINISTRATIVE UPDATE AND OPERATION OF  
NATURAL GAS COMPRESSOR AND/OR DEHYDRATION FACILITIES

APPLICATION NO.: G35-D107D

FACILITY ID: 033-00187

☐ CONSTRUCTION  
☒ MODIFICATION  
☐ RELOCATION

☐ CLASS I ADMINISTRATIVE UPDATE  
☐ CLASS II ADMINISTRATIVE UPDATE

### BACKGROUND INFORMATION

Name of Applicant (as registered with the WV Secretary of State's Office): MK Midstream Holdings, LLC

Federal Employer ID No. (FEIN): 47-1919654

Applicant's Mailing Address: 65 Professional Place

City: Bridgeport

State: WV

ZIP Code: 26330

Facility Name: PDC West Compressor Station

Operating Site Physical Address: 50 East Davisson Run Road  
If none available, list road, city or town and zip of facility.

City: Clarksburg

Zip Code: 26302

County: Harrison

Latitude & Longitude Coordinates (NAD83, Decimal Degrees to 5 digits):

Latitude: 39.275550

Longitude: -80.403099

SIC Code: 1311  
NAICS Code: 211111

Date Application Received:  
January 19, 2017

Fee Amount: \$4,000.00

Date Fee Received: November 22, 2016

Applicant Ad Date: January 24, 2017

Newspaper: The Exponent Telegram

Date Application Complete: February 8, 2017

Due Date of Final Action: March 19, 2017

Engineer Assigned: Roy F. Kees, P.E.

Description of Permitting Action: The purpose of this modification is to increase the flow rate on the two existing Dehydration Units to 67 mmscf/day on the Goff M&R, to replace two engines (CE-3R and CE-4R) with two engines of the same make and model (CE-7R and CE-8R), and add TK-3, TK-4, and TK-5.

## PROCESS DESCRIPTION

The following process description was taken from Registration Application G35-D107D:

Pipeline quality natural gas (dry) is supplied to six (6) 1380 BHP Caterpillar Internal combustion engine (CE-1R, CE-2R, CE-5R, CE-6R, CE-7R and CE-8R) each equipped Oxidation Catalytic Converters, for emission reductions. The engines drive compressors to move the natural gas through a pipeline into two (2) 67 MMCFD Tri-Ethylene Glycol (TEG) Dehydrators (TEG-1 and TEG-2) for drying the gas to below 7.0lbs/MMSCFD of Water Content and eventually into a sales line.

Produced liquid, which is mainly water with minimal levels of VOCs, from initial separation and dehydration, is stored within tanks TK-1 and TK-3. The produced liquids are transferred from the tanks to trucks via transfer hoses for off-site treatment/disposal. In addition, stormwater collected from the pads and oil collected from the compressors is stored in tanks TK-2, TK-4 and TK-5.

There are fugitive emissions associated with piping connection, valves and controllers. These emissions occur due to potential seepage from connections, flanges and open ended lines.

This permit modification includes:

- Increasing Glycol Dehydration units RSV-1 and RSV-2 from 31 mmscf/day and 45 mmscf/day to 67mmscf/day for both units
- Addition of the following Tanks:
  1. TK 3-100 bbl Tank used to collect produced water from Compressor CE-1R, CE-2R, CE-7R and CE-8R located on Goff Compressor Station
  2. TK-4 and TK-5 2 50 bbl tanks located on Cather Compressor Station to collect produced water from Compressor CE-5R and CE-6R
- Replacement of engines CE-3R and CE-4R with like-kind engines (CE-7R and CE-8R).

## SITE INSPECTION

Site Inspection Date: December 6, 2016

Site Inspection Conducted By: James Robertson

**Results of Site Inspection:** Facility appeared to be operating normally with no visual emissions or objectionable odors. Presently there are 4 compressor engines operating at the site labelled Goff West, 2 compressor engines operating at the site labelled Cather Station, and 2 GDU's operating at the site labelled M&R Station. All equipment falls under 033-00187.


Each of the sites are located along a relatively remote side road and are well over 300' away from any resident or other building. It is an existing site and in my opinion would be suitable for a Rule 13 permit or General Permit Registration.

Did Applicant meet Siting Requirements? Yes

If applicable, was siting criteria waiver submitted? N/A

**Directions to Facility:** From I-79 South; (1.) At exit 119, take ramp right for US-50 West toward Clarksburg, Travel 7.0 miles (2.) Turn left onto WV-98/Old US 50 / Sun Valley Rd. travel 0.4 miles (3.) turn left to stay on WV-98 and travel 0.3 miles (4.) arrive at the PDC West Compressor Station on the right.

Overhead Google Earth Image of Facility:



## ESTIMATE OF EMISSIONS BY REVIEWING ENGINEER

The following table indicates which methodology was used in the emissions determination:

Emission Unit ID#	Process Equipment	Calculation Methodology (e.g. ProMax, GlyCalc, mfg. data, AP-42, etc.)
CE-1R	Caterpillar G3516B LE Compressor Engine	Manufacturer Data / AP-42
CE-2R	Caterpillar G3516B LE Compressor Engine	Manufacturer Data / AP-42
CE-7R	Caterpillar G3516B LE Compressor Engine	Manufacturer Data / AP-42
CE-8R	Caterpillar G3516B LE Compressor Engine	Manufacturer Data / AP-42
CE-5R	Caterpillar G3608 TALE Compressor Engine	Manufacturer Data / AP-42
CE-6R	Caterpillar G3606 TALE Compressor Engine	Manufacturer Data / AP-42
RSV-1	Exterrann Dehydration Unit	Gly-Calc
RBV-1	Exterrann Reboiler	AP-42
RSV-2	Exterrann Dehydration Unit	Gly-Calc
RBV-2	Exterrann Reboiler	AP-42
TK-1	TEG / Produced Liquid	Site Specific Sample
TK-2	Oil Catch Storage Tank	Neg.
TK-3	Produced Liquid	Site Specific Sample
TK-4	Stormwater / Leaked Oils	Neg.
TK-5	Stormwater / Leaked Oils	Neg.
LO-1	Produced Water Loading	AP-42

The total facility PTE for the facility (including fugitive emissions) is shown in the following table:

Pollutant	Facility Wide PTE (tons/year)	PTE Change for Modification (tons/year)
Nitrogen Oxides	37.71	-9.80
Carbon Monoxide	36.44	+18.96
Volatile Organic Compounds	19.82	-7.52
Particulate Matter	1.07	-2.11
Particulate Matter-10/2.5	1.07	-2.11
Sulfur Dioxide	0.11	-0.10
Formaldehyde	7.53	-3.32
Total HAPs	8.08	-2.77
Carbon Dioxide Equivalent	26,598	0.00

Maximum detailed controlled point source emissions were calculated by the applicant and checked for accuracy by the writer and are summarized in the table on the next page.

APPLICANT: MK Midstream Holdings, LLC				FACILITY NAME: PDC West Compressor Station								G35-D107D			
Emission Point ID#	NO <sub>x</sub>		CO		VOC		SO <sub>2</sub>		PM <sub>10</sub>		PM <sub>2.5</sub>		GHG (CO <sub>2</sub> e)		
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	
CE-1R	1.01	4.41	0.48	2.11	0.03	0.15	0.00	0.01	0.00	0.00	0.00	0.00	386.18	1691.00	
CE-2R	1.07	4.69	0.17	0.75	0.06	0.26	0.00	0.01	0.00	0.00	0.00	0.00	386.18	1691.00	
CE-5R	1.06	4.66	0.05	0.22	0.08	0.35	0.00	0.02	0.00	0.00	0.00	0.00	663.22	2905.00	
CE-6R	0.86	3.78	0.06	0.28	0.04	0.19	0.00	0.01	0.00	0.00	0.00	0.00	496.72	2176.00	
CE-7R	1.52	6.66	3.70	16.19	1.46	6.40	0.01	0.03	0.11	0.50	0.11	0.50	1497.00	7634.00	
CE-8R	1.52	6.66	3.70	16.19	1.46	6.40	0.01	0.03	0.11	0.50	0.11	0.50	1497.00	7634.00	
RSV-1	--	--	--	--	0.67	2.96	--	--	--	--	--	--	210.00	920.00	
RBV-1	0.10	0.43	0.08	0.36	0.01	0.02	0.00	0.00	0.01	0.03	0.01	0.03	116.00	510.00	
RSV-2	--	--	--	--	0.67	2.95	--	--	--	--	--	--	1033.00	4522.00	
RBV-2	0.10	0.43	0.08	0.36	0.01	0.02	0.00	0.00	0.01	0.03	0.01	0.03	116.00	510.00	
TK-1	--	--	--	--	0.02	0.07	--	--	--	--	--	--	0.44	1.91	
TK-3	--	--	--	--	0.00	0.01	--	--	--	--	--	--	0.37	1.64	
LO-1	--	--	--	--	0.02	0.08	--	--	--	--	--	--	--	--	
Pigging, Blowdowns & Startup	--	--	--	--	--	4.18	--	--	--	--	--	--	--	--	
Fugitives	--	--	--	--	--	3.40	--	--	--	--	--	--	--	--	
TOTAL	7.23	31.71	8.32	36.44	4.52	27.44	0.03	0.11	0.24	1.07	0.24	1.07	5580.00	26598.00	

APPLICANT: MK Midstream Holdings, LLC			FACILITY NAME: PDC West Compressor Station										G35-D107D	
Emission Point ID#	Formaldehyde		Benzene		Toluene		Ethylbenzene		Xylenes		Hexane		Total HAPs	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
CE-1R	0.19	0.81	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.02	0.25	1.11
CE-2R	0.19	0.81	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.02	0.25	1.11
CE-5R	0.32	1.39	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.01	0.03	0.44	1.91
CE-6R	0.24	1.05	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.01	0.02	0.33	1.43
CE-7R	0.21	0.92	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.02	0.28	1.22
CE-8R	0.21	0.92	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.02	0.28	1.22
RSV-1	--	--	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.01	0.02	0.09	0.01	0.03
RBV-1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01
RSV-2	--	--	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.02	0.09	0.01	0.03
RBV-2	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01
TK-1	--	--	--	--	--	--	--	--	--	--	--	--	0.00	0.00
TK-3	--	--	--	--	--	--	--	--	--	--	--	--	0.00	0.00
LO-1	--	--	--	--	--	--	--	--	--	--	--	--	0.00	0.00
Pigging, Blowdowns & Startup	--	--	--	--	--	--	--	--	--	--	--	--	--	0.60
Fugitives	--	--	--	--	--	--	--	--	--	--	--	--	0.00	0.00
TOTAL	1.35	7.53	0.01	0.05	0.01	0.06	0.01	0.02	0.01	0.04	0.07	0.32	1.84	8.68

## REGULATORY APPLICABILITY

### 45CSR2 (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers)

The purpose of 45CSR2 (Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers) is to establish emission limitations for smoke and particulate matter which are discharged from fuel burning units.

45CSR2 states that any fuel burning unit that has a heat input under ten (10) MMBTU/hr is exempt from Sections 4 (weight emission standard), 5 (control of fugitive particulate matter), 6 (registration), 8 (testing, monitoring, recordkeeping, reporting) and 9 (startups, shutdowns, malfunctions). However, failure to attain acceptable air quality in parts of some urban areas may require the mandatory control of these sources at a later date. If the individual heat input of all of the proposed fuel burning units are below 10 MMBTU/hr, these units are exempt from the aforementioned sections of 45CSR2. However, the registrant would be subject to the opacity requirements in 45CSR2, which is 10% opacity based on a six minute block average. Fuel burning units greater than 10 MMBTU/hr are ineligible for registration under General Permit G35-D

Emission Unit ID#	Emission Unit Description	Maximum Design Heat Input (MDHI) (MMBTU/hr)
RBV-1	Reboiler	1.00
RBV-2	Reboiler	1.00

### 45CSR6 (To Prevent and Control Air Pollution from the Combustion of Refuse)

45CSR6 prohibits open burning, establishes emission limitations for particulate matter, and establishes opacity requirements. Sources subject to 45CSR6 include completion combustion devices, enclosed combustion devices, and flares.

The facility-wide requirements of the general permit include the open burning limitations §§45-6-3.1 and 3.2.

All completion combustion devices, enclosed combustion devices, and flares are subject to the particulate matter weight emission standard set forth in §45-6-4.1; the opacity requirements in §§45-6-4-3 and 4-4; the visible emission standard in §45-6-4.5; the odor standard in §45-6-4.6; and, the testing standard in §§45-6-7.1 and 7.2.

Enclosed combustion control devices and flares that are used to comply with emission standards of NSPS, Subpart OOOO are subject to design, operational, performance, recordkeeping and reporting requirements of the NSPS regulation that meet or exceed the requirements of 45CSR6.

Emission Unit ID#	Maximum Design Heat Input (MDHI) (MMBTU/hr)	Subject to Weight Emission Standard?	Control Efficiency Claimed by Registrant	Provide Justification how 45CSR6 is met.
N/A		<input type="checkbox"/> Yes <input type="checkbox"/> No		

#### 45CSR10 (To Prevent and Control Air Pollution from the Emission of Sulfur Oxides)

45CSR10 establishes emission limitations for SO<sub>2</sub> emissions which are discharged from stacks of fuel burning units. A “fuel burning unit” means and includes any furnace, boiler apparatus, device, mechanism, stack or structure used in the process of burning fuel or other combustible material for the primary purpose of producing heat or power by indirect heat transfer. Sources that meet the definition of “Fuel Burning Units” per 45CSR10-2.8 include GPUs, in-line heaters, heater treaters, and glycol dehydration unit reboilers.

Fuel burning units less than 10 MMBtu/hr are exempt. The sulfur dioxide emission standard set forth in 45CSR10 is generally less stringent than the potential emissions from a fuel burning unit for natural gas. The SO<sub>2</sub> emissions from a fuel burning unit will be listed in the G35-D permit registration at the discretion of the permit engineer on a case-by-case basis. Issues such as non-attainment designation, fuel use, and amount of sulfur dioxide emissions will be factors used in this determination. Fuel burning units greater than 10 MMBTU/hr are ineligible for registration under General Permit G35-D

Fuel burning units burning natural gas are exempt from Section 8 (Monitoring, Recording and Reporting) as well as interpretive rule 10A. The G35-D eligibility requirements exclude from eligibility any fuel burning unit that does not use natural gas as the fuel; therefore, there are no permit conditions for 45CSR10.

Emission Unit ID#	Emission Unit Description	Maximum Design Heat Input (MDHI) (MMBTU/hr)
RBV-1	Reboiler	1.00
RBV-2	Reboiler	1.00

#### 45CSR13 (Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Administrative Updates, Temporary Permits, General Permits, and Procedures for Evaluation)

45CSR13 applies to this source due to the fact that the applicant is defined as a “stationary source” under 45CSR13 Section 2.24.b. *Stationary source* means, for the purpose of this rule, any building, structure, facility, installation, or emission unit or combination thereof, excluding any emission unit which meets or falls below the criteria delineated in Table 45-13B which: (a) is subject to any substantive requirement of an emission control rule promulgated by the Secretary; (b) discharges or has the potential to discharge more than six (6) pounds per hour and ten (10) tons per year, or has the potential to discharge more than 144 pounds per calendar day, of any regulated air pollutant; (c) discharges or has the potential to discharge more than two (2) pounds per hour or five (5) tons per year of hazardous air pollutants considered on an aggregated basis; (d) discharges or has the potential to discharge any air pollutant(s) listed in Table 45-13A in the amounts shown in Table 45-13A or greater; or, (e) an owner or operator voluntarily chooses to be subject to a construction or modification permit pursuant to this rule, even though not otherwise required to do so. 45CSR13 has an original effective date of June 1, 1974.

The applicant meets the definition of a stationary source because (check all that apply):

- ☐ Subject to a substantive requirement of an emission control rule promulgated by the Secretary.
- ☒ Discharges or has the potential to discharge more than six (6) pounds per hour and ten (10) tons per year, or has the potential to discharge more than 144 pounds per calendar day, of any regulated air pollutant.
- ☐ Discharges or has the potential to discharge more than two (2) pounds per hour or five (5) tons per year of hazardous air pollutants considered on an aggregated basis.
- ☐ Discharges or has the potential to discharge any air pollutant(s) listed in Table 45-13A in the amounts shown in Table 45-13A or greater.
- ☐ Voluntarily chooses to be subject to a construction or modification permit pursuant to this rule, even though not otherwise required to do so.



General Permit G35-D Registration satisfies the construction, modification, relocation and operating permit requirements of 45CSR13. General Permit G35-D sets forth reasonable conditions that enable eligible registrants to establish enforceable permit limits.

Section 5 of 45CSR13 provides the permit application and reporting requirements for construction of and modifications to stationary sources. No person shall cause, suffer, allow or permit the construction, modification, relocation and operation of any stationary source to be commenced without notifying the Secretary of such intent and obtaining a permit to construct, modify, relocate and operate the stationary source as required in the rule or any other applicable rule promulgated by the Secretary.

If applicable, the applicant meets the following (check all that apply):

- ☐ Relocation
- ☒ Modification
- ☐ Class I Administrative Update (45CSR13 Section 4.2.a)
- ☐ Class II Administrative Update (45CSR13 Section 4.2.b)

#### **45CSR16 (Standards of Performance for New Stationary Sources Pursuant to 40 CFR Part 60)**

45CSR16 applies to all registrants that are subject to any of the NSPS requirements described in more detail in the Federal Regulations section. Applicable requirements of NSPS, Subparts IIII, JJJJ, OOOO and OOOOa are included in General Permit G35-D.

The applicant is subject to:

- ☐ 40CFR60 Subpart IIII
- ☒ 40CFR60 Subpart JJJJ
- ☒ 40CFR60 Subpart OOOO
- ☒ 40CFR60 Subpart OOOOa

#### **45CSR22 (Air Quality Management Fee Program)**

45CSR22 is the program to collect fees for certificates to operate and for permits to construct or modify sources of air pollution. 45CSR22 applies to all registrants. The general permit fee of \$500 is defined in 45CSR13. In addition to the application fee, all applicants subject to NSPS requirements or NESHAP requirements shall pay additional fees of \$1,000 and \$2,500, respectively.

Registrants are also required to obtain and have in effect a valid certificate to operate in accordance with 45CSR22 §4.1. The fee group for General Permit G35-D is Group 8D (natural gas compressor stations greater than 1,000 HP) with an annual operating fee of \$500 or 9M (all other sources) with an annual operating fee of \$200.

The applicant is in the following fee group:

- ☒ 8D (Natural Gas Compressor Stations Greater than 1,000 HP)
- ☐ 9M (All Other Sources)

**40CFR60 Subpart IIII (Standards of Performance for Stationary Compression Ignition Internal Combustion Engines)**

Subpart IIII sets forth non-methane hydrocarbon (NMHC), hydrocarbon (HC), nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), and particulate matter (PM) emission limits, fuel requirements, installation requirements, and monitoring requirements based on the year of installation of the subject internal combustion engine. The provisions for stationary compression ignition (CI) internal combustion engines for owners or operators of this Subpart have been included in General Permit G35-D, Section 12. The following CI engines are subject to this section:

Emission Unit ID#	Engine Description (Make, Model)	Engine Size (HP)	Date of Manufacture	Provide Justification how 40CFR60 Subpart IIII is met.
N/A				<input type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine

**40CFR60 Subpart JJJJ (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines)**

Subpart JJJJ sets forth nitrogen oxides (NO<sub>x</sub>), carbon monoxide (CO), and volatile organic compound (VOC) emission limits, fuel requirements, installation requirements, and monitoring requirements based on the year of installation of the subject internal combustion engine. The provisions for stationary spark ignition (SI) internal combustion engines for owners or operators of this Subpart have been included in General Permit G35-D, Section 12.

Emission Unit ID#	Engine Description (Make, Model)	Engine Size (HP)	Date of Manufacture	Provide Justification how 40CFR60 Subpart JJJJ is met.
CE-1R	Caterpillar G3516B	1380	>2010	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine
CE-2R	Caterpillar G3516B	1380	>2010	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine
CE-7R	Caterpillar G3516B	1380	1/16/12	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine
CE-8R	Caterpillar G3516B	1380	3/17/13	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine
CE-5R	Caterpillar G3608TALE	2370	4/11/11	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine
CE-6R	Caterpillar G3606TALE	1775	12/12/14	<input checked="" type="checkbox"/> Met Emission Standard <input type="checkbox"/> Certified Engine

**40CFR60, Subpart OOOO (Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution)**

EPA published its New Source Performance Standards (NSPS) and air toxics rules for the oil and gas sector on August 16, 2012. EPA published final amendments to the Subpart on September 23, 2013.

40CFR60 Subpart OOOO establishes emission standards and compliance schedules for the control of volatile organic compounds (VOC) and sulfur dioxide (SO<sub>2</sub>) emissions from affected facilities that commence construction, modification or reconstruction after August 23, 2011. The affected sources which commence construction, modification or reconstruction after August 23, 2011 are subject to the applicable provisions of this Subpart as described below:

***Centrifugal compressor affected facilities are included in General Permit G35-D, Section 10.0.***

Are there any applicable centrifugal compressor affected facilities not located at the well site?

☐ Yes      ☒ No

If Yes, list.

Engine Description (Make, Model)
N/A

Each centrifugal compressor affected facility, which is a single centrifugal compressor using wet seals that is located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A centrifugal compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this Subpart.

***Reciprocating compressor affected facilities are included in General Permit G35-D, Section 11.0.***

Are there any applicable reciprocating compressor affected facilities not located at the well site?

☒ Yes      ☐ No

If Yes, list.

Engine Description (Make, Model)
Caterpillar G3516B, CE-1R
Caterpillar G3516B, CE-2R
Caterpillar G3516B, CE-7R
Caterpillar G3516B, CE-8R
Caterpillar G3608TALE, CE-5R
Caterpillar G3606TALE, CE-6R

Each reciprocating compressor affected facility, which is a single reciprocating compressor located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A reciprocating compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this subpart.

***Pneumatic controllers affected facilities are included in General Permit G35-D, Section 9.0.***

Are there any applicable pneumatic controller affected facilities? ☐ Yes      ☒ No

For the natural gas production segment (between the wellhead and the point of custody transfer to the natural gas transmission and storage segment and not including natural gas processing plants), each pneumatic controller affected facility, which is a single continuous bleed natural gas-driven pneumatic controller operating at a natural gas bleed rate greater than 6 scfh.

**Requirements for storage vessel affected facilities are included in General Permit G35-D, Section 6.0.**  
**Determination of storage vessel affected facility status is included in Section 5.0 of General Permit G35-D.**

Are there any applicable storage vessel affected facilities? ☐ Yes ☒ No

If No, list any emission reduction devices and control efficiencies used to avoid 40CFR60 Subpart OOOO.

N/A

If Yes, list.

Emission Unit ID#	Storage Vessel Description	SV Size (gal)	Provide Justification how 40CFR60 Subpart OOOO is met.
N/A			

Each storage vessel affected facility, which is a single storage vessel located in the oil and natural gas production segment, natural gas processing segment or natural gas transmission and storage segment, and has the potential for VOC emissions equal to or greater than 6 tpy as determined according to this section by October 15, 2013 for Group 1 storage vessels and by April 15, 2014, or 30 days after startup (whichever is later) for Group 2 storage vessels. A storage vessel affected facility that subsequently has its potential for VOC emissions decrease to less than 6 tpy shall remain an affected facility under this subpart.

**40CFR60, Subpart OOOOa (Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution for which Construction, Modification or Reconstruction Commenced after September 18, 2015)**

EPA published its New Source Performance Standards (NSPS) and air toxics rules for the oil and gas sector on August 16, 2012. EPA published amendments to the Subpart on September 23, 2013 and June 3, 2016.

40CFR60 Subpart OOOOa establishes emission standards and compliance schedules for the control of the pollutant greenhouse gases (GHG). The greenhouse gas standard in this subpart is in the form of a limitation on emissions of methane from affected facilities in the crude oil and natural gas source category that commence construction, modification or reconstruction after September 18, 2015. This subpart also establishes emission standards and compliance schedules for the control of volatile organic compounds (VOC) and sulfur dioxide (SO<sub>2</sub>) emissions from affected facilities that commence construction, modification or reconstruction after September 18, 2015. The effective date of this rule is August 2, 2016.

For each compressor station, the registrant must reduce GHG (in the form of a limitation on emissions of methane) and VOC emissions by complying with fugitive emissions monitoring as required in §60.5397a and the alternative means of emission limitations in §60.5398a.

**Centrifugal compressor affected facilities are included in General Permit G35-D, Section 10.0.**

Are there any applicable centrifugal compressor affected facilities not located at the well site?

☐ Yes ☒ No

If Yes, list.

Engine Description (Make, Model)
N/A

Each centrifugal compressor affected facility, which is a single centrifugal compressor using wet seals that is located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A centrifugal compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this Subpart.

***Reciprocating compressor affected facilities are included in General Permit G35-D, Section 11.0.***

Are there any applicable reciprocating compressor affected facilities not located at the well site?

X Yes      ☐ No

If Yes, list.

Engine Description (Make, Model)
Caterpillar G3516B, CE-7R
Caterpillar G3516B, CE-8R

Each reciprocating compressor affected facility, which is a single reciprocating compressor located between the wellhead and the point of custody transfer to the natural gas transmission and storage segment. A reciprocating compressor located at a well site, or an adjacent well site and servicing more than one well site, is not an affected facility under this subpart.

***Pneumatic controllers affected facilities are included in General Permit G70-D, Section 10.0.***

Are there any applicable pneumatic controller affected facilities? ☐ Yes      ☒ No

Each pneumatic controller affected facility not located at a natural gas processing plant, which is a single continuous bleed natural gas-driven pneumatic controller operating at a natural gas bleed rate greater than 6 scfh.

***Requirements for storage vessel affected facilities are included in General Permit G70-D, Section 7.0.***

Are there any applicable storage vessel affected facilities? ☐ Yes      ☒ No

If No, list any emission reduction devices and control efficiencies used to avoid 40CFR60 Subpart OOOO.

N/A

If Yes, list.

Emission Unit ID#	Storage Vessel Description	SV Size (gal)	Provide Justification how 40CFR60 Subpart OOOO is met.
N/A			

Each storage vessel affected facility, which is a single storage vessel with the potential for VOC emissions equal to or greater than 6 tpy as determined according to this section.

***Fugitive Emissions GHG and VOC Standards affected facilities are included in General Permit G70-D in Section 12.0.***

Did the registrant commence construction, modification, or reconstruction of the compressor station after September 18, 2015 and is subject to §60.5397a? ☒ Yes      ☐ No

*For the purposes of §60.5397a, a "modification" to a compressor station occurs when one or more compressors is replaced by one or more compressors of greater total horsepower than the compressor(s) being replaced. The registrant must reduce GHG (in the form of a limitation on emissions of methane) and VOC emissions by complying with the requirements of paragraphs (a) through (j) of §60.5397a. These requirements are independent of the closed vent system and cover requirements in §60.5411a. These leak surveys must be conducted four (4) times per year.*

**40CFR63 Subpart HH (National Emission Standards for Hazardous Air Pollutants From Oil and Natural Gas Production Facilities)**

This Subpart applies to owners and operators of each triethylene glycol (TEG) dehydration unit that are located at oil and natural gas production facilities. Only area source requirements are included in General Permit G35-D, as defined in §63.761.

For area source applicability, the affected source includes each triethylene glycol (TEG) dehydration unit located at a facility that meets the criteria specified in §63.760(a).

Glycol dehydration unit(s) are included in General Permit G35-D, Section 14.0.

Are there any TEG dehydration unit(s) at this facility? ☒ Yes ☐ No

Are the TEG dehydration unit(s) located within an Urbanized Area (UA) or Urban Cluster (UC)?  
☐ Yes ☒ No

Are the glycol dehydration unit(s) exempt from 40CFR63 Section 764(d)? ☒ Yes ☐ No

If Yes, answer the following questions:

The actual annual average flowrate of natural gas to the glycol dehydration unit(s) is less than 85 thousand standard cubic meters per day, as determined by the procedures specified in §63.772(b)(1) of this Subpart. ☐ Yes ☒ No

The actual average emissions of benzene from the glycol dehydration unit process vent(s) to the atmosphere are less than 0.90 megagram per year (1 ton per year), as determined by the procedures specified in §63.772(b)(2) of this Subpart. ☒ Yes ☐ No

**40CFR63 Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines)**

Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This Subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations. This section reflects EPA's final amendments to 40 CFR part 63, Subpart ZZZZ that were issued on January 15, 2013 and published in the Federal Register on January 30, 2013.

WVDEP DAQ has delegation of the area source air toxics provisions of this Subpart requiring Generally Achievable Control Technology (GACT). The provisions of this Subpart have been included in this general permit under Section 12.0.

Emission Unit ID#	Engine Description (Make, Model)	Engine Size (HP)	Date of Manufacture	New or Existing under 40CFR63 Subpart ZZZZ?	Provide Justification how 40CFR63 Subpart ZZZZ is met.
CE-1R	Caterpillar G3516B	1380	>2010	New	JJJJ
CE-2R	Caterpillar G3516B	1380	>2010	New	JJJJ
CE-7R	Caterpillar G3516B	1380	1/16/12	New	JJJJ
CE-8R	Caterpillar G3516B	1380	3/17/13	New	JJJJ
CE-5R	Caterpillar G3608TALE	2370	4/11/11	New	JJJJ
CE-6R	Caterpillar G3606TALE	1775	12/12/14	New	JJJJ

Are there any engines that fall in the window of being new under 40CFR60 Subpart ZZZZ but manufactured before the applicability date in 40CFR60 Subpart JJJJ? ☐ Yes ☒ No

If so, list the engines: N/A

### SOURCE AGGREGATION DETERMINATION

"Building, structure, facility, or installation" is defined as all the pollutant emitting activities which belong to the same industrial grouping, are located on one or more contiguous and adjacent properties, and are under the control of the same person.

Is there equipment and/or activities used for onshore oil and natural gas production that are located on the same site, or on sites that share equipment and are within 1/4 mile of each other?

☐ Yes ☒ No

Is this equipment and/or activities under "common control"?

☒ Yes ☐ No

Do these facilities share the same two (2) digit SIC code?

☒ Yes ☐ No

#### ***Final Source Aggregation Decision.***

☒ Source not aggregated with any other source.

☐ Source aggregated with another source. List Company/Facility Name:

### RECOMMENDATION TO DIRECTOR

The information provided in the permit application, including all supplemental information received, indicates the applicant meets all the requirements of applicable regulations and the applicant has shown they meet the eligibility requirements of General Permit G35-D. Therefore, impact on the surrounding area should be minimized and it is recommended that the facility should be granted registration under General Permit G35-D.

Permit Engineer Signature: \_\_\_\_\_

Name and Title: Roy F. Kees, P.E. - Engineer, NSR Permitting

Date: February 8, 2017